

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

7006 Classic Denim Jacket for Children

Recommendations on fabric: firm fabric approx. 1.5 m (sizes 128–146), approx. 1.7 m (sizes 152–170), with a fabric width of 150 cm.

You will also need: fusible interfacing, 9 buttons.

CUTTING:



The word, “beam” used on some patterns means “straight of grain”. Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.

Seam allowances: all seams 1 cm.

Main fabric:

1. Center back piece – 1 piece on fold
2. Side back piece – 2 pieces
3. Back yoke – 1 piece
4. Front yoke – 2 pieces*
5. Center front piece – 2 pieces
6. Middle front piece – 2 pieces
7. Side front piece – 2 pieces
8. Front sleeve piece – 2 pieces

9. Back sleeve piece – 2 pieces
10. Collar – 2 pieces
11. Cuff – 2 pieces
12. Pocket welt – 2 pieces
13. Flap – 4 pieces
14. Waistband – 1 piece on fold
15. Large pocket bag – 2 pieces
16. Small pocket bag – 2 pieces

Fusible Interfacing:

1. Collar – 1 piece
2. Cuff – 2 pieces
3. Flap – 2 pieces
4. Pocket welt – 2 pieces
5. Waistband – 1 piece on fold

SEWING

1. Fuse interfacing to the wrong side of the corresponding fabric pieces. Also fuse interfacing to the wrong side of the cut front facings.
2. Sew the back pieces together, overlock the seam allowances, and press them toward the center. Sew the back yoke to the back piece, overlock the seam allowances, and press them upward. Topstitch 0.5 cm from the seams.
3. Sew the flap pieces together, right sides together, leaving the attachment edge open. Trim the seam allowances and clip the corners diagonally. Turn the flaps right side out and press. Topstitch 0.5 cm from the flap edges.
4. Sew the front pieces together, overlock the seam allowances, and press them toward the center. Topstitch 0.5 cm from the seams. Sew decorative stitching on the front as marked to imitate pockets. Attach the flaps to the front as marked and baste. Sew the front yoke to the front piece (with the flaps in between), overlock the seam allowances, and press them upward. Topstitch 0.5 cm from the seams.
5. Mark the welt pockets on the front as shown on the pattern. Fold and press the pocket welt along the center. Sew the small pocket bag to the wrong side of the welt. Sew the front edge of the welt along the lower marked pocket line. Sew the large pocket bag along the upper marked pocket line. Cut the pocket opening and clip diagonally toward the end of the seam, stopping 1 mm before the end of the opening. Turn the welt and pocket bags to the wrong side through the opening. Sew reinforcing stitches on the inside near the corners to secure the pocket ends. Sew the pocket bag edges together, overlock the seam allowances. Sew the second pocket in the same way.
6. Sew the shoulder and side seams, overlock the seam allowances, and press them

toward the back.

7. Fold the cut front facings toward the right side and sew the upper edges up to the center markings. Clip into the seam allowances at the markings. Turn the facings and press. Fold the inner edge of the facing under and sew it to the wrong side of the front piece.
8. Sew the collar pieces together, right sides together, leaving the attachment edge open. Trim the seam allowances and clip the corners diagonally. Turn the collar right side out and press. Topstitch 0.5 cm from the collar edges.
9. Sew the outer collar to the neckline of the jacket, right sides together. Trim the seam allowances and press them into the collar. Fold the inner collar edge inward and stitch it into the outer seam.
10. Sew the sleeve elbow seam up to the slit marking. Clip into the seam allowance on the front sleeve piece at the marking. Overlock the seam allowances and press them toward the back. Fold the slit seam allowance of the front sleeve piece to the wrong side and press. Topstitch 0.5 cm along the seams and slit.
11. Sew the remaining sleeve seams, overlock the seam allowances, and press them toward the back.
12. Set the sleeves into the armholes, overlock the seam allowances together, and press. Gather the lower edges of the back sleeve pieces.
13. Fold the cuffs lengthwise with right sides together and sew the short edges. Turn the cuffs right side out and press the edges. Sew one edge of the cuffs to the lower sleeve edges, right sides together. Press the seam allowances into the cuffs. Fold the inner cuff edge inward and stitch it into the outer seam.
14. Fold the waistband lengthwise with right sides together and sew the short edges. Turn the waistband right side out and press the edges. Sew one edge of the waistband to the lower edge of the jacket, right sides together. Press the seam allowances into the waistband. Fold the inner waistband edge inward and stitch it into the outer seam. Topstitch 0.5 cm from the waistband edges all the way around.
15. Make buttonholes in the right front piece, cuffs, and flaps as marked. Sew buttons to the left front piece, on the cuffs, and on the front under the flaps.

Congratulations – your jacket are finished! :)