

If the pattern has a double line around it, the seam allowances are included.

Note: By default, seam allowances are NOT included (single line) and will need to be added when laying out and cutting details.

Seam Allowance: 1 cm on all seams; hem guidelines are printed on pattern.

Important! Please print all the paper patterns and lay them out at the width of fabric you plan to use (usually from 90 to 150 cm) to see how much fabric you will need.

Don't forget to take into account pieces to be duplicated or cut on a fold. When sewing the garment, pay attention to notches. They must match up with corresponding pieces.

7127 Baby Dress with Long Sleeves and Round Neck

Recommendations on fabric: lightweight natural dress fabrics or fabrics with added synthetic fibers..

You will also need: invisible zipper.

CUTTING:

The word, "beam" used on some patterns means "straight of grain". Some pieces will be cut on the fold, this is noted on the pattern piece. Mark all notches and other design features such as darts, pleats etc. from the pattern onto your fabric.



Seam allowances: all seam allowances – 1 cm;
neckline, armhole, and sleeve cap – 0.7 cm; sleeve hem
and dress hem – 2 cm.

Tip: You can decorate the bodice of the dress with appliqués, rhinestones, or embroidery.

Main fabric:

1. Front – 1 piece
2. Back – 2 pieces
3. Sleeve – 2 pieces
4. Skirt – 2 pieces

INSTRUCTIONS:

1. Finish the center back edges. Insert the invisible zipper into the center back seam.
2. Sew and finish the side seams of the front and back.
3. Sew and finish the side seams of the skirt.
4. Along the upper edge of the skirt, sew a row of long gathering stitches. Gather the upper edge evenly along the entire width.
5. Place the upper part of the dress and the skirt right sides together and sew. Finish the seam.
6. Sew and finish the shoulder seams.
7. Finish the neckline edge. Turn the seam allowance to the wrong side and topstitch.
8. Sew and finish the sleeve seams.
9. Finish the sleeve hem. Turn the seam allowance to the wrong side and topstitch.
10. Set in the sleeves into the armholes, matching notches.
11. Finish the dress hem. Turn the seam allowance to the wrong side and topstitch.

Congratulations – your dress are finished! :)